

Social navigation: distance and grid-like codes support navigation of abstract social space in human brain

Reviewed Preprint

Revised by authors after peer review.

About eLife's process

Reviewed preprint version 2

February 28, 2024 (this version)

Reviewed preprint version 1

August 31, 2023

Sent for peer review

June 24, 2023

Posted to preprint server

June 10, 2023

Zilu Liang, Simeng Wu, Jie Wu, Wenxu Wang, Shaozheng Qin , Chao Liu 

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University • School of Systems Science, Beijing Normal University, Beijing, 100875, China

 https://en.wikipedia.org/wiki/Open_access

 Copyright information

Abstract

People form impressions about others during daily social encounters and infer personality traits from others' behaviors. Such trait inference is thought to rely on two universal dimensions, i.e., competence and warmth. These two dimensions can be used to construct a 'social cognitive map' organizing massive information obtained from social encounters efficiently. Originated from spatial cognition, the neural codes supporting representation and navigation of spatial cognitive map has been widely studied. Recent studies suggest similar neural mechanism subserves the map-like architecture in social cognition as well. Here we investigated how spatial codes operate beyond physical environment and support the representation and navigation of social cognitive map. We designed a social value space defined by two dimensions of competence and warmth. Behaviorally, participants were able to navigate to a learned location from random starting locations in this abstract social space. At neural level, we identified representation of distance in precuneus, fusiform gyrus and middle occipital gyrus. We also found partial evidence of grid-like representation patterns in medial prefrontal cortex and entorhinal cortex. Moreover, the intensity of grid-like response scaled with performance of navigating in social space and social avoidance trait scores. Our findings suggest a neurocognitive mechanism by which social information can be organized into a structured representation namely cognitive map and its relevance to social well-being.

eLife assessment

This study provides **useful** initial information on how humans represent two-dimensional abstract spaces in relation to the social traits of warmth and competence. While the study poses an interesting question, the evidence for a grid-like code at present is **incomplete**. This study will be of interest to researchers working in the field of spatial navigation as well as the navigation of conceptual abstract space.

Introduction

Countless daily social encounters pose people with the need to organize information about social encounters efficiently. Though people may ascribe a variety of traits to others, these inferences have been identified to rely on a few universal dimensions (Fiske et al., 2007 [↗](#); Stoller et al., 2020 [↗](#)). The most widely recognized dimensions are warmth, which concerns others intentions, and competence, which concerns others capability and possession of resources (Cuddy et al., 2008 [↗](#)). These universal dimensions can be used to construct a structured representation organizing impressions of other people or other social information alike, just like how one would specify a location in a plane using orthogonal dimensions for spatial navigation. Analogous to Tolman's original concept (Tolman, 1948 [↗](#)), here we termed this structured representation of social information about other people as 'social cognitive map', which may form the basis for social cognition. Having such a cognitive map for social perception is crucial. It helps us organize various experiences, track updates and guide novel inferences efficiently (Son et al., 2021 [↗](#)). Despite its importance in navigating social world, its neural underpinning remains under-investigated.

The resemblance between social and spatial cognitive map has led to the proposition that social cognitive map is also supported by similar mechanisms that map physical space (Schafer & Schiller, 2018 [↗](#)). In the domain of spatial navigation, it has been demonstrated that entorhinal grid cell activity supports representational coding of cognitive map. Direct recordings in rodents (Hafting et al., 2005 [↗](#)) and humans (Jacobs et al., 2013 [↗](#)) have found that the firing locations of grid cells form periodic triangular that covers the entire available arena during spatial navigation task. In this sense, grid cells form the basic units of a neural map of the spatial environment. One of the prominent properties of grid cells is their consistent grid orientation (i.e., the orientation of the grid relative to the environment) shared by neighboring grid cells (Hafting et al., 2005 [↗](#); Sargolini et al., 2006 [↗](#)). Moreover, the overlapping population formed by grid cells and head direction cells as well as conjunctive grid $\times$ head-direction cells in deeper layers of entorhinal cortex enables directional as well as positional tuning of the firing rate (Sargolini et al., 2006 [↗](#)). It has been proposed that this conjunctive representation at a population level can yield a directionally modulated firing pattern with hexagonal periodicity in which population activity is enhanced when agent's moving direction is aligned to the grid axes (Kriegeskorte & Storrs, 2016 [↗](#); Kunz et al., 2019 [↗](#)). Human studies using non-invasive neuroimaging techniques rely on this directional preference of populational conjunctive grid by head direction cell activity to detect evidence of grid-like code in fMRI BOLD signals during spatial navigation (Doeller et al., 2010 [↗](#)). Follow-up studies have reported entorhinal grid code during virtual as well as imagined navigation (Horner et al., 2016 [↗](#)), and even mental simulation (Bellmund et al., 2016 [↗](#)). More importantly, pioneering studies showed that the function of grid-like code goes beyond the scope of spatial navigation. Grid-like codes in entorhinal cortex and prefrontal cortex have been observed during nonspatial navigation such as perceptual (Aronov et al., 2017 [↗](#); Bao et al., 2019 [↗](#); Killian et al., 2012 [↗](#); Nau et al., 2018 [↗](#)), conceptual (Constantinescu et al., 2016 [↗](#)), semantic space (Vigano & Piazza, 2020 [↗](#); Vigano et al., 2021 [↗](#)) and more recently, discrete social hierarchy (Park et al., 2021 [↗](#)). Evidence from above studies converges into a domain-general role of grid-like codes that may play in organizing cognitive maps of various types including spatial and nonspatial domains (Bellmund et al., 2018 [↗](#)).

In this study, we tested the above hypothesis that social cognitive map is supported by a grid cell-like coding mechanism observed in spatial navigation. First, leveraging the theoretical framework of the stereotype content model, we set up an abstract two-dimensional social value map which are composed of competence and trustworthiness dimensions of social perception. Next, we adapted paradigms used in human fMRI grid-code study to test the hypothesis that grid-like codes and distance codes resembling those underpinning spatial navigation are involved in navigation in this abstract social space. Finally, to complete our argument that neural codes for social navigation subserve social cognition, we explored the link between neural codes during social navigation and social skills measured by navigational performance and social trait scores.

Results

To look for neural underpinnings of navigation in an abstract social space, we adapted a set of tasks from previous studies illustrating the relevance of grid-like code in navigating abstract concept space (Constantinescu et al., 2016 [↗](#)). Participants received intensive training on navigating in this abstract social space with precision. They completed a learning session, a review session during behavioral training on the first day, and a scanning session on the second day.

We designed the social value map, an abstract social space structuring one's social perception of other people's social value. It was defined by two ecologically important dimensions: competence and trustworthiness. A visualization with two adjacent bars enclosed by a square box was designed to represent the location on this social value map, with the height of each bar representing value of each dimension. We operationally defined these two dimensions under the framework of an investment game, in which trustee's social value is determined by the ability to earn profit (i.e., profit rate as competence) and the proportion of earnings returned to the investor (i.e., return rate as trustworthiness). We limited the range of competence and trustworthiness between 0 and 1. This made sure that the two dimensions are realistic (i.e., it is unlikely that a trustee will return you more than he/she has gained), and more importantly, orthogonal and share same metric system (cite paper on distorted grid field). Participants played the role of an investor in this investment task (**Figure S1A**) at the very beginning of the experiment to develop a concrete understanding of the visual analogue and the quantitative meaning of these two dimensions.

Six avatars with different levels of competence and trustworthiness (**Figure 1A** [↗](#)), in analogy to landmarks in the physical environment, were placed on the social value map of size 1 unit $\times$ 1 unit which was in accordance with the range of competence and trustworthiness. The current spatial arrangement aimed to make avatars distinguishable on both dimensions while spreading widely across the whole space. Specifically, each participant's set of avatars' coordinates was sampled within circles of 1/30-unit radius around center coordinates (**Figure 1B** [↗](#)). Avatars were represented by standard photographs of real human faces. Photographs were matched on competence and trustworthiness ratings based on rating data collected online via Qualtrics in an independent sample of participants (**Supplementary Methods**). Additionally, participants in the current sample also completed rating on the selected faces before the experiment and after the fMRI scan to reassure that the used face stimuli did not elicit biased social perception and to test whether participants learned each avatar's characteristics and updated their social perception accordingly.

In the training, participants explored the vast social space by morphing the bars with different competence: trustworthiness ratio using the non-spatial controller to look for the six avatars (**Figure S1C**). Morphing the bars resembles making a transition in the social space in that it was done by two steps: 1) deciding a trajectory to follow by changing the competence: trustworthiness ratio using the non-spatial controller, 2) how further along to follow that trajectory. No prior information about the characteristics of the avatars was provided to the participants. Thus, participants could only explore social space as if they were looking for landmarks in a newly introduced physical environment. An avatar would pop out when the visualization matched his/her characteristics. Specifically, the avatar would pop out when participants' current location fell within a 0.01-unit radius of the correct location on the social value map. In this way, participants not only learned the characteristics of each avatar but also became familiar with the whole space even though this map-like structure was never revealed to them.

After participants were fully acquainted with the avatars and the social space, a set of tasks were used to test if participants learned the avatars, and more importantly, if they formed an internal representation of the social value map, even though the map-like structure was never directly revealed to them. The first one was the collect task (**Figure S1D**) which required participant to navigate to the location of the avatars from random starting locations in the abstract space. In




Figure 1.

Experimental Design and Behavioral Performance.

(A) Visual analogues illustrating each avatar's social values. Height of the left bars signals values on competence dimension, while height of the right bars signals trustworthiness. Labels for each of the two bars are omitted for illustration purpose. (B) Corresponding layout of the social value map and example trajectory in recall task. Scattered dots indicate the actual sets of positions generated for participants. (C) Positions of the avatars indicated by participants at the end of the whole experiment. (D) Trial timeline of the recall task. Participants first watched the bars morphing for one second according to a predefined competence-trustworthiness ratio (i.e., the first half of a trajectory in Figure 1B). After the bars stopped morphing, they were instructed to imagine the bars continue to morph according to the same ratio, at the same speed and for the same amount of time. (i.e., the second half of a trajectory in Figure 1B). (E) Color-coded trajectory map of the explore task during learning and review session. Color indicated the percentage of time spent in each pixel of the social value map during the explore task in the learning (left panel) and review (right panel) session. A pattern emerged that participants spent more time at avatars and less time at edge during review. (F) Memory test performance of the collect and recall task in learning, review and scan-day session. (G) The distance effect in comparison task across the review and scan-day session. Colored dots indicated the estimates of distance effect regressor while error bars indicated standard error of the estimates. (H) Ratings became predictable from the avatars' social value after experiment. Icons of avatars are for illustration and retrieved from <https://pixabay.com/vectors/avatar-flat-modern-minimal-5261900/>, <https://pixabay.com/vectors/avatar-flat-modern-minimal-5261896/>.

each trial, they were instructed to morph the box on the left to match the characteristic of the avatar shown on the right. Specifically, we asked participants to make as few transitions as possible. Two performance indices were calculated: 1) the deviation of participant's first transition from the ideal trajectory; and 2) the Euclidean distance between the location corresponding to participants' morphed bars and the avatar's actual location in the abstract space. The second one was the recall task, which required participant to mentally traverse the abstract social space according to a half-seen trajectory and identify the destination that follows (**Figure 1D**). In each trial, participants were first shown the two bars morphing according to a predefined competence: trustworthiness ratio for 1 second. The bars then stopped morphing, and participants were instructed to imagine the bars keep morphing according to the same ratio, at the same speed, and for the same amount of time. After this, participants had to choose which of the three given options matched the bars after imagination. Essentially, each trial is a trajectory vector defined by moving direction (i.e., morphing ratio) and travelled distance on the social value map. Participants' recall accuracies were taken as performance index. We investigated the neural representation of the trajectory in each trial while participant perform this task. The third one was the compare task which required participants to compare different pairs of avatars on one given dimension (competence and trustworthiness) or by a fair combination of both dimensions (willingness to cooperate). Under the assumption that participant's accuracy and response time would be moderated by the similarity between the avatars, we predicted that participants would be less accurate and take longer time when comparing avatars with closer distance on the given dimension than when comparing avatars far apart if they represent the six avatars in the 2D space (similar to the inferential distance effect in ordered relationships (Potts, 1974)). The final one was the map task at the end of the experiment in which participants were informed about the map-like structure and were asked to indicate the location of each avatar on an empty social value map using mouse click.

Participants construct social value map after associative learning of avatars and corresponding characteristics

Participants were successful in reconstructing such a layout in a map task at the end of experiment (**Figure 1C**). Linear mixed effect models revealed that participants' performance in tasks significantly improved over sessions. In the explore task, it took them significantly less time to find all avatars in the review session ($\beta_{\text{session}} = -67.589$, $t = -37.604$, $p < 0.001$). They also spent much less time at edge ($\beta = -0.104$, $t = -9.070$, $p < 0.001$) and more time at avatars ($\beta_{\text{session}} = 0.023$, $t = 7.367$, $p < 0.001$) during exploration in the review session (**Figure 1E**). Likewise, performance indices suggest evident improvement in collect and recall task as training progressed (**Figure 1F**, Percentage of first transition deviation $< 15^\circ$ in recall task: $\beta_{\text{session}} = 0.050411$, $t = 3.2187$, $p = 0.002$; Percentage of distance within 0.01 in recall task: $\beta_{\text{session}} = 0.047$, $t = 3.002$, $p = 0.003$; Accuracy in recall task: $\beta_{\text{session}} = 0.020$, $t = 4.213$, $p < 0.001$). Furthermore, participants were able to form an implicit map-like structure and integrate both dimensions when making decisions between avatars. In the compare task, linear mixed effect models revealed significant effect of distance between avatars in the compared dimension on response time and accuracy as predicted (**Figure 2G**, all $p < 0.001$). Lastly, learning induced changes in participants' ratings on avatars on all rating items (competence, trustworthiness, and attractiveness) (**Figure 2H**, **Table S1A**). There was no preference over the six presented faces when participants were naïve to the social value of different avatars (**Table S1B**, all $p > 0.890$), but their ratings became significantly dissociable according to the learned social value at the end of the experiment (**Table S1B**, all $p < 0.001$). These results indicated successful formation of a 2D social map by associating each avatar with respective social value.




Figure 2.

Neural representation of Euclidian distance on the social value map.

(A) Activity in the bilateral Precuneus positively correlated with travelled Euclidian distance. (B) Activity in bilateral Fusiform and the right middle occipital gyrus negatively correlated with travelled Euclidian distance. Display threshold: cluster-defining threshold $p < 0.001$.

Precuneus and fusiform jointly encode Euclidian distance during social navigation

Next, we investigated the neural representations supporting the social cognitive map. To examine the neural code for distance information, we conducted whole-brain analysis with a GLM in which travelled Euclidian distance (i.e., the length of each trial's trajectory vector) was entered as parametric modulator of the morph stage regressor.

This analysis revealed two marginally significant clusters in the precuneus whose activity positively correlated with travelled distance on the social value map (**Figure 2A**, **Table S2A**, right precuneus: peak coordinate $[x, y, z] = [12, -56, 26]$, $t(37) = 4.952$, $p = 0.056$ FWE-corrected; left precuneus: peak coordinate $[x, y, z] = [-12, -54, 18]$, $t(37) = 4.530$, $p = 0.058$ FWE-corrected; cluster-defining threshold $p < 0.001$ FWE-corrected). Interestingly, we also observed negative correlation between travelled distance and activity of clusters in several regions, including bilateral fusiform gyrus (**Figure 2B**, **Table S2B**, right fusiform: peak coordinate $[x, y, z] = [36, -48, -20]$, $t(37) = 5.912$, $p < 0.001$ FWE-corrected; left fusiform: peak coordinate $[x, y, z] = [-38, -56, -10]$, $t(37) = 4.724$, $p = 0.008$ FWE-corrected) and the right middle occipital gyrus (**Figure 2B**, **Table S2B**, peak coordinate $[x, y, z] = [34, -68, 20]$, $t(37) = 4.649$, $p = 0.018$ FWE-corrected; cluster-defining threshold $p < 0.001$).

Grid-like activity aligned to prefrontal and entorhinal grid orientation

The whole-brain quadrature filter analysis served as a functional localizer and identified several regions sensitive to hexagonal modulation, independent of grid orientation (**Table S3**). Thus, we defined spherical ROIs with a 5-mm radius centered at each of the peak coordinate to estimate the grid orientation of each ROI. As no region in the entorhinal cortex survived this analysis, we defined four entorhinal ROI based on subdivisions from anatomical mask (Maass et al., 2015). We then conducted the leave-one-out cross-validation analysis to test for the grid orientation consistency effect.

Of all the grid orientations derived from the above ROIs, we only found a hexagonally modulated effect aligned to the grid orientation of the ROI in the right frontal pole (right FP) cluster (**Figure 3B**, peak coordinate $[x, y, z] = [26, 52, -2]$, $t(37) = 4.494$, cluster-level $p = 0.017$ FWE-corrected, cluster-defining threshold $p < 0.001$) and the grid orientation of the anatomically defined right posterior-medial entorhinal cortex (right pmEC, **Figure 3C**). For the right FP grid orientation, whole-brain analysis revealed this alignment effect in bilateral ventral medial prefrontal cortex (vmPFC, **Figure 3D** left and middle panel, peak coordinate $[x, y, z] = [-14, 56, -12]$, $t(37) = 4.245$, cluster-level $p = 0.033$ FWE-corrected, cluster-defining threshold $p < 0.005$) and the left entorhinal cortex (left EC) extending to the parahippocampus region (**Figure 3E** left and middle panel, peak coordinate $[x, y, z] = [-16, -22, -26]$, $t(37) = 4.563$, cluster-level $p = 0.024$ FWE-corrected, cluster-defining threshold $p < 0.005$). For the right pmEC grid orientation, significant alignment effect was found in two clusters in bilateral vmPFC (**Figure 3F** left and middle panel, right rectus: peak coordinate $[x, y, z] = [10, 34, -18]$, $t(37) = 4.908$, cluster-level $p = 0.033$ FWE-corrected; left ACC: peak coordinate $[x, y, z] = [-8, 32, 6]$, $t(37) = 4.810$, cluster-level $p = 0.009$ FWE-corrected; cluster-defining threshold $p < 0.005$) and one cluster in right superior temporal pole (right STP, **Figure 3G** left and middle panel, peak coordinate $[x, y, z] = [36, 20, -30]$, $t(37) = 4.962$, cluster-level $p = 0.018$ FWE-corrected, cluster-defining threshold $p < 0.005$). However, we did not find evidence of grid-like code in the entorhinal cortex aligned to its own putative grid orientation either with this orientation estimation approach (**Figure S5A-B**) or with the representation similarity analysis approach (**Figure S5C-D**).




Figure 3.

Evidence of grid-like activity aligned to putative grid orientation in the right frontal pole and the right posterior-medial entorhinal cortex

(A) Theoretical prediction of grid-like activity **(B-C)** ROIs for deriving putative grid orientations: **(B)** right FP ROI from quadrature filter analysis showing sensitivity to hexagonal modulation. A 5-mm sphere was defined around the peak coordinate to compute grid angle. Display threshold: voxel-level $p < 0.001$, cluster-level $p < 0.05$ FWE-corrected. **(C)** Anatomically defined right pmEC ROI used to compute grid angle. **(D-G)** Grid like activity aligned to putative grid orientations in the right FP ROI **(D-E)** and right pmEC **(F-G)** ROI respectively. Left panels: clusters from whole-brain hexagonal consistency analysis. Color indicates T statistics as shown in the colorbar in **B**. Display threshold: voxel-level $p < 0.005$, cluster-level $p < 0.05$ FWE-corrected. Middle panels: hexagonal consistency effects plotted as contrast estimates of the 12 trial-bin regressors extracted from corresponding cluster in the left panel; To illustrate effect in EC in **E**, estimates were extracted from the intersection of the suprathreshold cluster and anatomical mask of EC. Right panels: such effects were specific to six-fold. Notes: n.s., $p > 0.05$, * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$. Abbreviations: FP, frontal pole; pmEC, posterior-medial entorhinal cortex; vmPFC, ventral medial prefrontal cortex; STP, superior temporal pole.

One important assumption underlying the univariate analysis for grid-like code in human fMRI data is neighboring grid cells share similar grid orientation. Consistent with previous studies, we examined this assumption in our dataset by testing the distribution of putative voxel-wise grid orientations in the right FP ROI and in the right pmEC ROI for each participant. This revealed a clustered distribution of voxel-wise grid orientations in FP ROI (V-test, all $p < 0.011$, except in one participant's one estimating set $p = 0.176$; see **Figure S2A** for representative participants). Previous studies have also shown that grid orientations across participants tend to distribute uniformly. This has been replicated in the right FP ROI in our dataset (**Figure S3** left panel, Rayleigh's tests for nonuniformity, all $p > 0.782$). However, in the pmEC ROI, these results are less consistent. With regards to voxel-wise orientations, 31 participants show the above clustered distribution (V-test, all $p < 0.040$; see **Figure S2B** for representative participants), but there are 7 participants each of whom has at least one estimating set that didn't pass the statistical test (V-test, all $p > 0.068$). Across participants, only grid orientations from two estimating sets conformed to the uniform distribution (**Figure S3** right panel, Rayleigh's tests for nonuniformity, run 1,2,3: $p = 0.010$, run 1,2,4: $p = 0.019$).

For completeness, we tested the specificity of hexagonal modulation. That is, the identified alignment effect only exists with six-fold periodicity. The above orientation estimation and cross-validation procedure was repeated for each of the four controlled periodicity (i.e., 4-fold, 5-fold, 7-fold, and 8-fold). Signals were extracted from the clusters that showed significant hexagonal consistency. One-sample t-tests showed that signals within these clusters were not modulated by any of the controlled periodicities and paired t-test showed that six-fold periodicity in general showed greater alignment effect (**Figure 3D-G**, right panels). In sum, our univariate analysis revealed that the vmPFC and left EC showed six-fold specific grid-like code aligned to right FP's grid orientation and that the vmPFC and right STP showed six-fold specific grid-like code aligned to right pmEC's grid orientation.

Behavioral relevance of spatial codes for the social value map

Additionally, we explored whether these identified grid-like code could have any behavioral relevance beyond the scanned task. We quantify this using several indices that can be classified into two categories. The first category of indices reflects participants ability to make decision based on the social value map, i.e., the distance effect in the compare task. Specifically, we focused on the distance effect during the cooperation block when participants decide the avatar they are more willing to cooperate with by taking into account both dimensions. This is essentially the beta weight of the distance regressor in predicting participant's accuracy and log-transformed response time. The second category of indices reflects participants' social trait, including social anxiety and social avoidance scores. We tested the behavioral relevance of grid-like code by entering the above indices as covariates into the second-level analysis when testing grid orientation consistency effect, and all covariates were tested in separate regression models.

Whole-brain analysis revealed significant clusters in the temporal lobe whose consistency effect scaled with distance effect in response time. For grid orientation of right FP ROI (**Figure 4A**), hexagonal consistency effect in the left middle temporal gyrus and right Lingual gyrus correlated with the distance effect (left middle temporal gyrus: peak coordinate $[x, y, z] = [-36, -70, 8]$, $t(37) = 4.528$, cluster-level $p < 0.001$ FWE-corrected; right Lingual gyrus: peak coordinate $[x, y, z] = [-38, -66, 4]$, $t(37) = 4.369$, cluster-level $p < 0.001$ FWE-corrected; cluster-defining threshold $p < 0.005$). For grid orientation of right pmEC ROI (**Figure 4B**), hexagonal consistency effect in bilateral Lingual correlated with the distance effect (left Lingual gyrus: peak coordinate $[x, y, z] = [-12, -68, -2]$, $t(37) = 4.355$, cluster-level $p = 0.077$ FWE-corrected; right Lingual gyrus: peak coordinate $[x, y, z] = [16, -62, -2]$, $t(37) = 3.934$, cluster-level $p = 0.032$ FWE-corrected; cluster-defining threshold $p < 0.005$). In general, greater distance effect in the comparison task was correlated with greater hexagonal consistency in temporal lobe aligned to both prefrontal and entorhinal grid orientations. In addition, this analysis also revealed a significant cluster in the left precuneus/posterior cingulate

cortex (PCC), and its consistency effect aligned to the right FP grid orientation (**Figure 4C**, peak coordinate $[x, y, z] = [0, -64, 28]$, $t(37) = 4.965$, cluster-level $p < 0.001$ FWE-corrected, cluster-defining threshold $p < 0.001$) was negatively correlated with social avoidance score.

Discussion

In this study, we investigated whether cognitive map in social cognition domain recruit the neural processing mechanism similar to its spatial counterpart. We identified distance representation in precuneus, fusiform gyrus and middle occipital gyrus. In addition, we demonstrated some evidence of grid-like activity in prefrontal cortex and entorhinal cortex. Furthermore, we explored the behavioral relevance of grid-like activity in temporal pole and precuneus.

When participants were mentally traversing a predefined social value map, we found that activities in the bilateral precuneus were positively correlated with travelled distance, while activities in bilateral FFG and right MOG were negatively correlated with travelled distance. In spatial navigation literature, though intracranial electroencephalography studies have shown the relevance of hippocampal theta oscillation in encoding travelled distance, neural correlates of travelled distance at macroscopic level using fMRI are relatively sparsely investigated (Kunz et al., 2019). Patai et al. (2019) showed that retrosplenial cortex positively correlated with path distance in that greater distance is associated with increased precuneus activity and that this effect remained robust after controlling for Euclidean distance. Likewise, we showed that precuneus activity was positively correlated with travelled Euclidean distance during implicit navigation in the abstract social space. Moreover, the present peak coordinates coincide with those reported in a previous study by Park et al. (2020). In their study, participants learned 2D social hierarchy (competence and popularity) of two groups of agents and were asked to perform a transitive inference task in which compare a pair of agents on their competence or popularity. The authors found that bilateral precuneus represented pairwise difference in the task-relevant dimension instead of pairwise Euclidean distance in the two-dimension space. Another study reported that posterior cingulate cortex/precuneus tracks the length of the vector of social relationship change, i.e., an egocentric distance (Tavares et al., 2015). Taken together, we speculate that precuneus may encode the distance of the route, either on a concrete or an abstract map, that participants trespass under task demand. Less clear is the negative correlation we observed between travelled distance and activity in fusiform as well as middle occipital gyrus. Both FFG and MOG are involved during human spatial navigation (Boccia et al., 2014). In particular, fusiform gyrus extending into the parahippocampal place area has been showed to involve in processing spatial information such as landmark and orientation cues (Qiu et al., 2019). However, to our knowledge, there is no study that reports such negative distance coding in these occipitotemporal regions during navigation.

Apart from the distance code, another focus of the current study was to test whether grid-like codes support the organization of social knowledge. Previous studies on reporting grid-like codes mostly report hexagonal modulated pattern in the entorhinal cortex and medial prefrontal regions aligned to putative grid orientation from both regions (Constantinescu et al., 2016). Our current study partly replicated these findings, most of which are in the prefrontal region. In terms of prefrontal orientation, whole-brain analysis revealed alignment effects in the bilateral vmPFC and left EC. In terms of entorhinal orientation, however, alignment effect was found in the bilateral vmPFC and right superior temporal pole, but not in entorhinal cortex. Though we found evidence of prefrontal grid-like codes subserving social navigation, its origin remains elusive. Up to date, there has been no significant evidence of grid-like neuronal tuning in this area (Wikenheiser et al., 2021). Jacobs et al. (2013) examined grid-like cells in a variety of brain regions including the frontal cortex in neurosurgical patients during a virtual navigation task, but the proportion of significant grid-like cells in the frontal cortex did not exceed type I error rate (they did identify grid-like cells in cingulate cortex which is posterior to the prefrontal regions).




Figure 4.

Behavioral relevance of hexagonal consistency effect.

(A-B) Higher hexagonal consistency in temporal lobe aligned to grid orientation of (A) right FP ROI and (B) right pmEC significantly correlated with stronger distance effect in compare task when choosing preferred partners for cooperation. Display threshold: voxel-level $p < 0.005$, cluster-level $p < 0.05$ FWE-corrected. (C) Hexagonal consistency effect in left Precuneus aligned to grid orientation of right FP ROI significantly correlated with social avoidance score. Display threshold: voxel-level $p < 0.001$, cluster-level $p < 0.05$ FWE-corrected. Notes: n.s., $p > 0.05$, * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$. Abbreviations: FP, frontal pole; pmEC, posterior-medial entorhinal cortex; MTG, middle temporal gyrus; LING, lingual gyrus.

Therefore, it is less likely that prefrontal grid-like codes reported in our study and previous literature come from grid cells in the prefrontal cortex. A more plausible explanation is that the anatomically and functionally connected medial- and orbitofrontal cortex and entorhinal cortex (Navarro Schroder et al., 2015; Peng et al., 2018; Squire & Zola, 1996) coordinated together to support flexible decision making. However, adopting both univariate and multivariate approaches, our current study did not find reliable effect of hexagonal grid-like code in the entorhinal region aligned to its own grid orientation, which should be evident if such hypothesis stands. Previous studies postulated that lack of univariate evidence of grid-like code may have to do with low signal-to-noise ratio (tSNR) in data from the entorhinal cortex (Bao et al., 2019). Indeed, we found lower mean tSNR in all four entorhinal sub regions compared to the frontal pole cluster from the quadrature filter analysis (**Supplementary Methods, Figure S6A**). But we did not identify a significant relationship between tSNR and the z-transformed F statistics of hexagonal modulation either across participants or within participants (**Supplementary Methods, Figure S6B-C, Table S4**). Thus, we cannot conclude that low signal-to-noise ratio in entorhinal cortex led to this null finding in our study.

Nonetheless, our study did provide some incomplete evidence of grid-like activity in the entorhinal cortex and prefrontal region while participants were mentally trespassing an abstract social space. Grid codes are proposed to provide a metric of space (Moser & Moser, 2008) and underly the process of path integration (McNaughton et al., 2006). Previous studies have suggested that entorhinal grid codes are capable of representing space even at a higher level of abstraction that goes beyond spatial navigation to support cognitive flexibility in general (Bellmund et al., 2018). Existing literature revealed correlation between entorhinal and prefrontal grid-like code and performance in spatial, perceptual and conceptual space. Indeed, our exploratory analysis showed that the univariate hexagonal consistency effect in temporal lobe scaled with the distance effect in a comparison task block when participants chose their preferred partner for future cooperation. The distance effect reflected the extent to which participants relied their preference judgment on the pairwise distance between given pair of avatars. As we explicitly required participants to take both dimension into consideration, it reflected participant's ability to plan a route between landmarks (which represents retained impression of social encounters) in the abstract social space. This is very similar to what Park et al. (2021) reported in their recent study. In this study, participants were trained on the rankings of 16 individuals on two dimensions (competence and popularity) separately, then they were asked to make comparisons between novel pairings unseen during training. Replicating their previous findings (Park et al., 2020), the authors found that the entorhinal and hippocampus system successfully reconstruct the unseen whole spectrum of social hierarchies as a 2D cognitive map. Moreover, they found that grid-like representations support trajectories of novel inferences on this 2D cognitive map that underpins decision making. Park's study and ours differed in that they focused on discrete relational structures whilst we constructed a continuous social space. Collectively, these evidence support the notion that grid-like codes underpin navigation in an abstract social cognitive map, be it discrete or continuous.

Intriguingly, our study found that the intensity of hexagonal modulation in precuneus aligned to estimated grid orientation of prefrontal region is negatively correlated with participants' social avoidance tendency. While previous studies mainly reported grid-like codes in the entorhinal cortex and prefrontal cortex and its relevance to spatial navigation deficit in clinically risky population (Kunz et al., 2015), to the best of our knowledge, no report has shown the psychological relevance of grid-like code outside these classical regions to potential social deficit. One study of direct neuronal recording revealed grid-like neuronal activity in patients' cingulate cortex during virtual spatial navigation task (Jacobs et al., 2013), implying that the human grid-cell network previously focused around entorhinal and prefrontal region also extends to the cingulate cortex. However, our study did not find evidence of grid-like pattern in precuneus. Thus, we cannot conclude that our result points to a direct relationship between precuneus grid-like code and social functionality. Meanwhile, precuneus, as a core node of the DMN, has abundant

neuroanatomical connections with prefrontal regions (Greicius et al., 2009 [↗](#); Khalsa et al., 2014 [↗](#); Oane et al., 2020 [↗](#)). Precuneus has also been reported to show a decrease in resting-state connectivity to parahippocampal gyrus and medial prefrontal cortex in patients with SAD (Yuan et al., 2018 [↗](#)). Therefore, it is likely that downstream projections from the OFC/vmPFC motivated the observed correlation pattern in our study.

In conclusion, our present study demonstrates that navigating in a continuous social space recruited distance codes and grid-like codes in brain regions reported by spatial navigation studies and their behavioral and psychological relevance. Our findings further strengthen the notion that neural mechanisms involved in spatial cognitive map may play a domain-general role in maintaining abstract, structured representation of knowledge that support flexible cognitive behavior.

Our study has a few limitations. First, to make our study comparable to those investigating representation of abstract nonsocial knowledge, our scanner task investigate social navigation in a static environment and no social interaction or social decision is involved. Further studies should be conducted to investigate how such structured representation of social knowledge is reused and updated during social decisions and social interactions. Second, we specifically designed the abstract social value map to be formed by two orthogonal dimensions that have the same scale. This allows us to examine grid-like activity pattern with six-fold periodicity unambiguously. But this set-up may lack generality. For one thing, it is unlikely that all parts of the whole social value space span by the warmth and competence dimension are equally important. Social ties are more likely to be formed among human alike (McPherson et al., 2001 [↗](#)) and human show the tendency to represent ingroup members more differentially than outgroup members (Hugenberg et al., 2010 [↗](#); Ostrom et al., 1993 [↗](#)), so it is likely that some area of the social value space is represented in finer granularity than other. In spatial navigation, entorhinal grid cells showed sensitivity to geometric and environmental features, and the resulting distorted grid fields no longer form a regular hexagonal lattice and fail to show six-fold periodicity (Derdikman et al., 2009 [↗](#); He & Brown, 2019 [↗](#); Krupic et al., 2015 [↗](#)). For instance, grid fields has been found to sometimes warp towards reward (Boccarda et al., 2019 [↗](#)). In this sense, spontaneous social value space may bear more resemblance to such kind of reward map covered by distorted grid fields rather than a regular, uniform square/circular open arena where six-fold symmetric grid-like coding was originally identified. For another, the geometric properties of social and non-social cognitive space in real life can be very different from that of the physical space in navigation. Our knowledge of other people in real life is often high-dimensional integrating multi-modal information from sensory features (face, voice etc.) to social cognitive information (hobbies, social status, etc.). Moreover, while dimensions of physical space (the cartesian axes) are orthogonal and their metrics are on the same scale, the dimensions of social perception in real life may not be orthogonal and may be incomparable. The stereotype content model predicted that there is a weak but low correlation between warmth and competence (Cuddy et al., 2009 [↗](#)) and other studies have found there exists compensation between these dimensions (Kervyn et al., 2010 [↗](#)). To the best of our knowledge, it remains elusive whether and how grid cells can represent such high-dimensional space with non-orthonormal basis and how the univariate and multivariate analysis pipeline used to identify grid-like coding in fMRI signal could be revised to address these concerns. Taken together, the intrinsic social cognitive map in which human structure their knowledge of others may be non-uniform, high-dimensional and have non-orthonormal dimensions. Future studies would need to take this into account and explore beyond the six-fold grid-like activity pattern in regular 2D space.

Materials and Methods

Participants

No power analysis was done to pre-determine the sample size. Instead, we tried to achieve a sample size comparable to previous studies investigating grid-like representations using fMRI (Doeller et al., 2010). 44 participants (18 males, mean age $\pm$ standard deviation: 21.59 $\pm$ 2.56) recruited from surrounding universities finished all behavioral training and fMRI scanning in the current study at the Beijing Normal University Imaging Center for Brain Research (BICBR). Each participant underwent intensive behavioral training (including one learning session and one review session) and one fMRI scanning session (**Figure S1F**). Three participants were excluded from all further analyses due to excessive head motion in the scanner (framewise displacement greater than 3mm). Another three participants failing to achieve satisfactory behavioral accuracies (lower than 60%) in the scanning session were excluded from all further analyses. The remaining 38 participants' data were included in the behavioral and fMRI analysis reported in the main text (15 males, mean age $\pm$ standard deviation: 21.47 $\pm$ 2.64).

The study was approved by the ethics committee of National Key Laboratory of Cognitive Neuroscience and Learning at Beijing Normal University (ICBIR_A_0071_011). All regulations were followed, and participants signed paper-form informed consent before the experiment. Participants received monetary compensation for their participation in the current study.

Data acquisition

Behavioral data acquisition

Behavioral tasks were programmed using Psychophysics Toolbox-3 in MATLAB or E-prime 2.0. Online pilot rating study, pre- and post-experiment questionnaires were collected via Qualtrics.

MRI data acquisition

We acquired T2-weighted functional images on a 3T SIEMENS MAGNETOM Prisma scanner with a 64-channel head coil. We acquired 33 slices, 3mm thick with: repetition time (TR) = 2000ms, echo time (TE) = 30ms, flip angle = 90°, field of view (FoV) = 224 mm, voxel size = 3.5 $\times$ 3.5 $\times$ 3.5 mm³. To correct for spatial distortion, a field map was acquired with dual echo-time images covering the whole brain with the following parameters: TR = 400ms, TE1 = 4.92ms, TE2 = 7.38ms, flip angle = 60°, FoV = 224mm, voxel size = 3.5 $\times$ 3.5 $\times$ 3.5 mm³. A T1-weighted structural image was acquired with the following parameters: TR = 2530ms, TE = 2.98ms, flip angle = 7°, FoV = 256mm, voxel size = 0.5 $\times$ 0.5 $\times$ 1 mm³.

Data analysis

All analyses were performed with customized code in MATLAB and R.

Pre-processing of functional MRI data

Pre-processing of functional MRI data was done with SPM12. Functional images were spatially realigned to the first image in the time series and corrected for slice-timing. Spatial distortion based on field map. The T1-weighted structure image was co-registered to the mean aligned functional image, segmented and normalized to MNI space. The derived transformation parameters from structural image normalization were applied to normalize realigned functional images. Finally, smoothing was done with a 6mm full-width half-maximum Gaussian kernel.

Searching for representation of distance on 2D social value map in human fMRI signal

To look for neural representation of the travelled distance on the social value map, we conducted a whole-brain univariate analysis. Two regressors were included in this GLM, one modeling the morph stage and one modeling the choice stage. The travelled Euclidian distance during morph stage was entered as a parametric modulator for the morph-stage regressor.

Searching for grid-like representations of 2D social value map in human fMRI signal

To search for evidence of entorhinal and prefrontal grid-like activity supporting representation of social space, we further implemented two popular approaches to examine hexa-directional coding with fMRI data at the morphing stage in each trial. The first one is the orientation-estimation approach (Bellmund et al., 2018 [DOI](#); Doeller et al., 2010 [DOI](#)) based on univariate analysis. In this approach, we first defined Regions of Interest (ROIs) that were sensitive to hexagonal modulation using univariate analysis (see **Supplementary Methods** for details). Thereafter, with a leave-one-out cross-validation procedure, we tested for hexagonal modulation aligned to grid orientation of the ROIs for each participant. In this procedure, we split the four acquired functional scanning runs into an ‘estimating set’ and a ‘testing set’.

The estimating set consisted of three runs and was used to calculate the grid orientation of the ROIs (see **Supplementary Methods** for details). The remaining one run then served as the testing set where the alignment effect was tested with the inferred grid orientation. This procedure was repeated four times to independently yield the inferred orientations for each run. Specifically, we divided trials into 12 bins of 30° according to the offset of trial trajectory from the putative grid orientation (**Figure 3A** [DOI](#) left panel). The theoretical prediction for grid-like code is that neural signal should be stronger in trials aligned than misaligned to the grid orientation (0° modulo 60° vs 30° modulo 60°). In other words, activation should be higher in the aligned (odd-numbered) bins than the misaligned (even-numbered) bins (**Figure 3B** [DOI](#) right panel). In addition to the above region-wise orientations, we also derived voxel-wise putative grid orientations in each ROI and used the circulate statistics to test whether there were clustered distributions of grid orientations as observed by the direct neuron recordings. As we failed to find evidence of grid-like activity in EC aligned to its own putative grid orientation using the first approach, we took the anatomical mask of EC (Maass et al., 2015 [DOI](#)) and explored grid-like activity using a multivariate approach. This approach leverages representational similarity analysis (RSA) and is widely adopted based on the assumption that a distributed coding scheme is employed by the entorhinal cortex. To start with, we estimated trial-specific activation for each trial in each run using the ‘Least Squares Separate’ (LSS) approach (Abdulrahman & Henson, 2016 [DOI](#); Mumford et al., 2012 [DOI](#)). This approach built separate GLMs for each trial with one target regressor modeling the current trial of interest and a second nuisance regressor modeling the rest. Beta estimates of the target regressors were extracted from the entorhinal ROI as trial-specific activity pattern for each of the 320 trials (**Figure S4A**). We then tested whether this multivariate pattern is hexagonally modulated. Though the exact implementations varied slightly across studies, they fell into the following two categories according to their dependence on the estimated putative grid orientation. The ‘orientation-independent’ approach (**Figure S4B**) tested the hypotheses that multivariate pattern similarity between trajectory pairs is proportional to the angular difference between their moving direction modulated by 60° (Bellmund et al., 2016 [DOI](#); Vigano & Piazza, 2020 [DOI](#); Vigano et al., 2021 [DOI](#)), which is done by calculation the correlation between the derived neural dissimilarity matrix and the model matrix. The ‘orientation-dependent’ approach (**Figure S4C**) leveraged the assumption that if activity in a given ROI is aligned to a preferred orientation, the similarity of multivoxel patterns in this region should be higher for aligned trial-pairs than that between aligned and misaligned trial-pairs (Bao et al., 2019 [DOI](#)). Grid-orientations were calculated as described in the previous section using the leave-one-out cross-validation procedure. Trials were then classified into aligned

and misaligned trials according to the angular difference between trajectories and the estimated entorhinal grid orientation. We then computed the similarities between aligned-aligned trial pairs (AA pairs) and aligned-misaligned trial pairs (AM pairs). By subtracting similarity between AM pairs from AA pairs, we yielded an index for difference between pattern similarity of the two trial-pair types for each participant. One-sample t-test was used to test whether similarity between AM pairs was significantly lower than that of AA pairs. All representational similarity analyses were based on non-smoothed fMRI data.

Data Availability

We have published preprocessed smoothed and unsmoothed functional MRI data, the code to run the experiment and the code to run the univariate analysis reported in the main text. Dataset and code are publicly available at <https://doi.org/10.57760/sciencedb.08637> .

Acknowledgements

We are grateful for the volunteers who participated in this study. We thank Alexandra Constantinescu for providing helpful information regarding the experiment design in their previous study. We thank Kelou Jin for his hard work and help when conducting pilot experiments. We thank Shen Zhang and Huagen Wang for their help in data analysis. This work was supported by the National Natural Science Foundation of China (32271092 and 32130045), the Major Project of National Social Science Foundation (19ZDA363), the Beijing Municipal Science and Technology Commission (Z151100003915122), the National Program for Support of Top-notch Young Professionals.

Author contributions

Zilu Liang, Conceptualization, Investigation, Formal analysis, Visualization, Writing – original draft, Writing – review and editing; Simeng Wu, Investigation; Jie Wu, Investigation; Wenxu Wang, Conceptualization; Shaozheng Qin, Conceptualization, Supervision, Writing – review and editing; Chao Liu, Conceptualization, Supervision, Writing – review and editing, Funding acquisition.

References

- Abdulrahman H., Henson R. N. (2016) **Effect of trial-to-trial variability on optimal event-related fMRI design: Implications for Beta-series correlation and multi-voxel pattern analysis** *Neuroimage* **125**:756–766 <https://doi.org/10.1016/j.neuroimage.2015.11.009>
- Aronov D., Nevers R., Tank D. W. (2017) **Mapping of a non-spatial dimension by the hippocampal entorhinal circuit** *Nature* **543**:719–722 <https://doi.org/10.1038/nature21692>
- Bao X., Gjorgieva E., Shanahan L. K., Howard J. D., Kahnt T., Gottfried J. A. (2019) **Grid-like Neural Representations Support Olfactory Navigation of a Two-Dimensional Odor Space** *Neuron* **102**:1066–1075 <https://doi.org/10.1016/j.neuron.2019.03.034>
- Bellmund J. L., Deuker L., Navarro Schroder T., Doeller C. F. (2016) **Grid-cell representations in mental simulation** *Elife* **5** <https://doi.org/10.7554/eLife.17089>
- Bellmund J. L. S., Gardenfors P., Moser E. I., Doeller C. F. (2018) **Navigating cognition: Spatial codes for human thinking** *Science* **362** <https://doi.org/10.1126/science.aat6766>
- Boccaro C. N., Nardin M., Stella F., O'Neill J., Csicsvari J. (2019) **The entorhinal cognitive map is attracted to goals** *Science* **363**:1443–1447 <https://doi.org/10.1126/science.aav4837>
- Boccia M., Nemmi F., Guariglia C. (2014) **Neuropsychology of environmental navigation in humans: review and meta-analysis of FMRI studies in healthy participants** *Neuropsychol Rev* **24**:236–251 <https://doi.org/10.1007/s11065-014-9247-8>
- Constantinescu A. O., O'Reilly J. X., Behrens T. E. J. (2016) **Organizing conceptual knowledge in humans with a gridlike code** *Science* **352**:1464–1468 <https://doi.org/10.1126/science.aaf0941>
- Cuddy A. J. *et al.* (2009) **Stereotype content model across cultures: towards universal similarities and some differences** *Br J Soc Psychol* **48**:1–33 <https://doi.org/10.1348/014466608X314935>
- Cuddy A. J. C., Fiske S. T., Glick P. (2008) **Cuddy, A. J. C., Fiske, S. T., & Glick, P. (2008). Warmth and Competence as Universal Dimensions of Social Perception: The Stereotype Content Model and the BIAS Map. In (pp. 61-149). 10.1016/s0065-2601(07)00002-0** [https://doi.org/10.1016/s0065-2601\(07\)00002-0](https://doi.org/10.1016/s0065-2601(07)00002-0)
- Derdikman D., Whitlock J. R., Tsao A., Fyhn M., Hafting T., Moser M. B., Moser E. I. (2009) **Fragmentation of grid cell maps in a multicompartment environment** *Nat Neurosci* **12**:1325–1332 <https://doi.org/10.1038/nn.2396>
- Doeller C. F., Barry C., Burgess N. (2010) **Evidence for grid cells in a human memory network** *Nature* **463**:657–661 <https://doi.org/10.1038/nature08704>
- Fiske S. T., Cuddy A. J., Glick P. (2007) **Universal dimensions of social cognition: warmth and competence** *Trends Cogn Sci* **11**:77–83 <https://doi.org/10.1016/j.tics.2006.11.005>

- Greicius M. D., Supekar K., Menon V., Dougherty R. F. (2009) **Resting-state functional connectivity reflects structural connectivity in the default mode network** *Cereb Cortex* **19**:72–78 <https://doi.org/10.1093/cercor/bhn059>
- Hafting T., Fyhn M., Molden S., Moser M. B., Moser E. I. (2005) **Microstructure of a spatial map in the entorhinal cortex** *Nature* **436**:801–806 <https://doi.org/10.1038/nature03721>
- He Q., Brown T. I. (2019) **Environmental Barriers Disrupt Grid-like Representations in Humans during Navigation** *Curr Biol* **29**:2718–2722 <https://doi.org/10.1016/j.cub.2019.06.072>
- Horner A. J., Bisby J. A., Zotow E., Bush D., Burgess N. (2016) **Grid-like Processing of Imagined Navigation** *Curr Biol* **26**:842–847 <https://doi.org/10.1016/j.cub.2016.01.042>
- Hugenberg K., Young S. G., Bernstein M. J., Sacco D. F. (2010) **The categorization-individuation model: an integrative account of the other-race recognition deficit** *Psychol Rev* **117**:1168–1187 <https://doi.org/10.1037/a0020463>
- Jacobs J. *et al.* (2013) **Direct recordings of grid-like neuronal activity in human spatial navigation** *Nat Neurosci* **16**:1188–1190 <https://doi.org/10.1038/nn.3466>
- Kervyn N., Yzerbyt V., Judd C. M. (2010) **Compensation between warmth and competence: Antecedents and consequences of a negative relation between the two fundamental dimensions of social perception** *European Review of Social Psychology* **21**:155–187 <https://doi.org/10.1080/13546805.2010.517997>
- Khalsa S., Mayhew S. D., Chechacz M., Bagary M., Bagshaw A. P. (2014) **The structural and functional connectivity of the posterior cingulate cortex: comparison between deterministic and probabilistic tractography for the investigation of structure-function relationships** *Neuroimage* **102**:118–127 <https://doi.org/10.1016/j.neuroimage.2013.12.022>
- Killian N. J., Jutras M. J., Buffalo E. A. (2012) **A map of visual space in the primate entorhinal cortex** *Nature* **491**:761–764 <https://doi.org/10.1038/nature11587>
- Kriegeskorte N., Storrs K. R. (2016) **Grid Cells for Conceptual Spaces?** *Neuron* **92**:280–284 <https://doi.org/10.1016/j.neuron.2016.10.006>
- Krupic J., Bauza M., Burton S., Barry C., O’Keefe J. (2015) **Grid cell symmetry is shaped by environmental geometry** *Nature* **518**:232–235 <https://doi.org/10.1038/nature14153>
- Kunz L., Maidenbaum S., Chen D., Wang L., Jacobs J., Axmacher N. (2019) **Mesosopic Neural Representations in Spatial Navigation** *Trends Cogn Sci* **23**:615–630 <https://doi.org/10.1016/j.tics.2019.04.011>
- Kunz L. *et al.* (2015) **Reduced grid-cell-like representations in adults at genetic risk for Alzheimer’s disease** *Science* **350**:430–433 <https://doi.org/10.1126/science.aac8128>
- Maass A., Berron D., Libby L. A., Ranganath C., Duzel E. (2015) **Functional subregions of the human entorhinal cortex** *Elife* **4** <https://doi.org/10.7554/eLife.06426>
- McNaughton B. L., Battaglia F. P., Jensen O., Moser E. I., Moser M. B. (2006) **Path integration and the neural basis of the ‘cognitive map’** *Nat Rev Neurosci* **7**:663–678 <https://doi.org/10.1038/nrn1932>

- McPherson M., Smith-Lovin L., Cook J. M. (2001) **Birds of a Feather: Homophily in Social Networks** *Annual Review of Sociology* **27**:415–444 <https://doi.org/10.1146/annurev.soc.27.1.415>
- Moser E. I., Moser M. B. (2008) **A metric for space** *Hippocampus* **18**:1142–1156 <https://doi.org/10.1002/hipo.20483>
- Mumford J. A., Turner B. O., Ashby F. G., Poldrack R. A. (2012) **Deconvolving BOLD activation in event-related designs for multivoxel pattern classification analyses** *Neuroimage* **59**:2636–2643 <https://doi.org/10.1016/j.neuroimage.2011.08.076>
- Nau M., Navarro Schroder T., Bellmund J. L. S., Doeller C. F. (2018) **Hexadirectional coding of visual space in human entorhinal cortex** *Nat Neurosci* **21**:188–190 <https://doi.org/10.1038/s41593-017-0050-8>
- Navarro Schroder T., Haak K. V., Zaragoza Jimenez N. I., Beckmann C. F., Doeller C. F. (2015) **Functional topography of the human entorhinal cortex** *Elife*, **4** <https://doi.org/10.7554/eLife.06738>
- Oane I. *et al.* (2020) **Cingulate cortex function and multi-modal connectivity mapped using intracranial stimulation** *Neuroimage* **220** <https://doi.org/10.1016/j.neuroimage.2020.117059>
- Ostrom T. M., Carpenter S. L., Sedikides C., Li F. (1993) **Differential processing of in-group and out-group information** *Journal of Personality and Social Psychology* **64**:21–34 <https://doi.org/10.1037/0022-3514.64.1.21>
- Park S. A., Miller D. S., Boorman E. D. (2021) **Inferences on a multidimensional social hierarchy use a grid-like code** *Nat Neurosci* **24**:1292–1301 <https://doi.org/10.1038/s41593-021-00916-3>
- Park S. A., Miller D. S., Nili H., Ranganath C., Boorman E. D. (2020) **Map Making: Constructing, Combining, and Inferring on Abstract Cognitive Maps** *Neuron* **107**:1226–1238 <https://doi.org/10.1016/j.neuron.2020.06.030>
- Patai E. Z. *et al.* (2019) **Hippocampal and Retrosplenial Goal Distance Coding After Long-term Consolidation of a Real-World Environment** *Cereb Cortex* **29**:2748–2758 <https://doi.org/10.1093/cercor/bhz044>
- Peng L., Zeng L. L., Liu Q., Wang L., Qin J., Xu H., Shen H., Li H., Hu D. (2018) **Functional connectivity changes in the entorhinal cortex of taxi drivers** *Brain Behav* **8** <https://doi.org/10.1002/brb3.1022>
- Potts G. R. (1974) **Storing and retrieving information about ordered relationships** *Journal of Experimental Psychology* **103**:431–439 <https://doi.org/10.1037/h0037408>
- Qiu Y., Wu Y., Liu R., Wang J., Huang H., Huang R. (2019) **Representation of human spatial navigation responding to input spatial information and output navigational strategies: An ALE meta-analysis** *Neurosci Biobehav Rev* **103**:60–72 <https://doi.org/10.1016/j.neubiorev.2019.06.012>
- Sargolini F., Fyhn M., Hafting T., McNaughton B. L., Witter M. P., Moser M. B., Moser E. I. (2006) **Conjunctive representation of position, direction, and velocity in entorhinal cortex** *Science* **312**:758–762 <https://doi.org/10.1126/science.1125572>

- Schafer M., Schiller D. (2018) **Navigating Social Space** *Neuron* **100**:476–489 <https://doi.org/10.1016/j.neuron.2018.10.006>
- Son J. Y., Bhandari A., FeldmanHall O. (2021) **Cognitive maps of social features enable flexible inference in social networks** *Proc Natl Acad Sci U S A* **118** <https://doi.org/10.1073/pnas.2021699118>
- Squire L. R., Zola S. M. (1996) **Structure and function of declarative and nondeclarative memory systems** *Proc Natl Acad Sci U S A* **93**:13515–13522 <https://doi.org/10.1073/pnas.93.24.13515>
- Stolier R. M., Hehman E., Freeman J. B. (2020) **Trait knowledge forms a common structure across social cognition** *Nat Hum Behav* **4**:361–371 <https://doi.org/10.1038/s41562-019-0800-6>
- Tavares R. M., Mendelsohn A., Grossman Y., Williams C. H., Shapiro M., Trope Y., Schiller D. (2015) **A Map for Social Navigation in the Human Brain** *Neuron* **87**:231–243 <https://doi.org/10.1016/j.neuron.2015.06.011>
- Tolman E. C. (1948) **Cognitive maps in rats and men** *Psychol Rev* **55**:189–208 <https://doi.org/10.1037/h0061626>
- Vigano S., Piazza M. (2020) **Distance and Direction Codes Underlie Navigation of a Novel Semantic Space in the Human Brain** *J Neurosci* **40**:2727–2736 <https://doi.org/10.1523/JNEUROSCI.1849-19.2020>
- Vigano S., Rubino V., Soccio A. D., Buiatti M., Piazza M. (2021) **Grid-like and distance codes for representing word meaning in the human brain** *Neuroimage* **232** <https://doi.org/10.1016/j.neuroimage.2021.117876>
- Wikenheiser A. M., Gardner M. P. H., Mueller L. E., Schoenbaum G. (2021) **Spatial Representations in Rat Orbitofrontal Cortex** *J Neurosci* **41**:6933–6945 <https://doi.org/10.1523/JNEUROSCI.0830-21.2021>
- Yuan C. *et al.* (2018) **Precuneus-related regional and network functional deficits in social anxiety disorder: A resting-state functional MRI study** *Compr Psychiatry* **82**:22–29 <https://doi.org/10.1016/j.comppsy.2017.12.002>

Article and author information

Zilu Liang

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University
ORCID iD: [0009-0009-3446-5117](https://orcid.org/0009-0009-3446-5117)

Simeng Wu

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University

Jie Wu

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University

Wenxu Wang

School of Systems Science, Beijing Normal University, Beijing, 100875, China

Shaozheng Qin

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University

For correspondence: szqin@bnu.edu.cn

Chao Liu

State Key Laboratory of Cognitive Neuroscience and Learning & IDG/McGovern Institute for Brain Research, Beijing Normal University

For correspondence: liuchao@bnu.edu.cn

Copyright

© 2023, Liang et al.

This article is distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use and redistribution provided that the original author and source are credited.

Editors

Reviewing Editor

Floris de Lange

Donders Institute for Brain, Cognition and Behaviour, Nijmegen, Netherlands

Senior Editor

Floris de Lange

Donders Institute for Brain, Cognition and Behaviour, Nijmegen, Netherlands

Reviewer #1 (Public Review):

This study examines whether the human brain uses a hexagonal grid-like representation to navigate in a non-spatial space constructed by competence and trustworthiness. To test this, the authors asked human participants to learn the levels of competence and trustworthiness for six faces by associating them with specific lengths of bar graphs that indicate their levels in each trait. After learning, participants were asked to extrapolate the location from the partially observed morphing bar graphs. Using fMRI, the authors identified brain areas where activity is modulated by the angles of morphing trajectories in six-fold symmetry. The strength of this paper lies in the question it attempts to address. Specifically, the question of whether and how the human brain uses grid-like representations not only for spatial navigation but also for navigating abstract concepts, such as social space, and guiding everyday decision-making. This question is of emerging importance.

I acknowledge the authors' efforts to address the comments received. However, my concerns persist:

(1) The authors contend that shorter reaction times correlated with increased distances between individuals in social space imply that participants construct and utilize two-dimensional representations. This method is adapted from a previous study by Park et al. Yet, there is a fundamental distinction between the two studies. In the prior work, participants learned relationships between adjacent individuals, receiving feedback on their decisions,

akin to learning spatial locations during navigation. This setup leads to two different predictions: If participants rely on memory to infer relationships, recalling more pairs would be necessary for distant individuals than for closer ones. Conversely, if participants can directly gauge distances using a cognitive map, they would estimate distances between far individuals as quickly as for closer ones. Consequently, as the authors suggest, reaction times ought to decrease with increasing decision value, which, in this context, corresponds to distances. However, the current study allowed participants to compare all possible pairs without restricting learning experiences, rendering the application of the same methodology for testing two-dimensional representations inappropriate. In this study, the results could be interpreted as participants not forming and utilizing two-dimensional representations.

(2) The confounding of visual features with the value of social decision-making complicates the interpretation of this study's results. It remains unclear whether the observed grid-like effects are due to visual features or are genuinely indicative of value-based decision-making, as argued by the authors. Contrary to the authors' argument, this issue was not present in the previous study (Constantinescu et al.). In that study, participants associated specific stimuli with the identities of hidden items, but these stimuli were not linked to decision-making values (i.e., no image was considered superior to another). The current study's paradigm is more akin to that of Bao et al., which the authors mention in the context of RSA analysis. Indeed, Bao et al. controlled the length of the bars specifically to address the problem highlighted here. Regrettably, in the current paradigm, this conflation remains inseparable.

(3) While the authors have responded to comments in the public review, my concerns noted in the Recommendation section remain unaddressed. As indicated in my recommendations, there are aspects of the authors' methodology and results that I find difficult to comprehend. Resolving these issues is imperative to facilitate an appropriate review in subsequent stages.

Considering that the issues raised in the previous comments remain unresolved, I have retained my earlier comments below for review.

The weak points of this paper are that its findings are not sufficiently supporting their arguments, and there are several reasons for this:

(1) Does the grid-like activity reflect 'navigation over the social space' or 'navigation in sensory feature space'? The grid-like representation in this study could simply reflect the transition between stimuli (the length of bar graphs). Participants in this study associated each face with a specific length of two bars, and the 'navigation' was only guided by the morphing of a bar graph image. Moreover, any social cognition was not required to perform the task where they estimate the grid-like activity. To make social decision-making that was conducted separately, we do not know if participants needed to navigate between faces in a social space. Instead, they can recall bar graphs associated with faces and compute the decision values by comparing the length of bars. Notably, in the trust game in this study, the competence and trustworthiness are not equally important to make a decision (Equation 1). The expected value is more sensitive to one over the other. This also suggests that the space might not reflect social values but the perceptual differences.

(2) Does the brain have a common representation of faces in a social space? In this study, participants don't need to have a map-like representation of six faces according to their levels of social traits. Instead, they can remember the values of each trait. The evidence of neural representations of the faces in a 2-dimensional social space is lacking. The authors argued the relationship between the reaction times and the distances between faces provides evidence of the formation of internal representations. However, this can be found without the internal representation of the relationships between faces. If the authors seek internal representations of the faces in the brain, it would be important to show that this representation is not simply driven by perceptual differences between bar graphs that participants may recall in association with each face.

Considering these caveats, it is hard for me to agree if the authors provide evidence to support their claims.

<https://doi.org/10.7554/eLife.89025.2.sa2>

Reviewer #2 (Public Review):

Summary:

In this work, Liang et al. investigate whether an abstract social space is neurally represented by a grid-like code. They trained participants to 'navigate' around a two-dimensional space of social agents characterized by the traits warmth and competence, then measured neural activity as participants imagined navigating through this space. The primary neural analysis consisted of three procedures: 1) identifying brain regions exhibiting the hexagonal modulation characteristic of a grid-like code, 2) estimating the orientation of each region's grid, and 3) testing whether the strength of the univariate neural signal increases when a participant is navigating in a direction aligned with the grid, compared to a direction that is misaligned with the grid. From these analyses, the authors find the clearest evidence of a grid-like code in the prefrontal cortex and weaker evidence in the entorhinal cortex.

Strengths:

The work demonstrates the existence of a grid-like neural code for a socially-relevant task, providing evidence that such coding schemes may be relevant for a variety of two-dimensional task spaces.

Weaknesses:

In the revised manuscript, the authors soften their claims about finding a grid code in the entorhinal cortex and provide additional caveats about limitations in their findings. It seems that the authors and reviewers are in agreement about the following weaknesses, which were part of my original review: Claims about a grid code in the entorhinal cortex are not well-supported by the analyses presented. The whole-brain analysis does not suggest that the entorhinal cortex exhibits hexagonal modulation; the strength of the entorhinal BOLD signal does not track the putative alignment of the grid code there; multivariate analyses do not reveal any evidence of a grid-like representational geometry.

In the authors' response to reviews, they provide additional clarification about their exploratory analyses examining whether behavior (i.e., reaction times) and individual difference measures (i.e., social anxiety and avoidance) can be predicted by the hexagonal modulation strength in some region X, conditional on region X having a similar estimated grid alignment with some other region Y. My guess is that readers would find it useful if some of this language were included in the main text, especially with regard to an explanation regarding the rationale for these exploratory studies.

<https://doi.org/10.7554/eLife.89025.2.sa1>

Reviewer #3 (Public Review):

Liang and colleagues set out to test whether the human brain uses distance and grid-like codes in social knowledge using a design where participants had to navigate in a two-dimensional social space based on competence and warmth during an fMRI scan. They showed that participants were able to navigate the social space and found distance-based codes as well as grid-like codes in various brain regions, and the grid-like code correlated with behavior (reaction times).

On the whole, the experiment is designed appropriately for testing for distant-based and grid-like codes, and is relatively well powered for this type of study, with a large amount of behavioral training per participant. They revealed that a number of brain regions correlated positively or negatively with distance in the social space, and found grid-like codes in the frontal polar cortex and posterior medial entorhinal cortex, the latter in line with prior findings on grid-like activity in entorhinal cortex. The current paper seems quite similar conceptually and in design to previous work, most notably Park et al., 2021, Nature Neuroscience.

(1) The authors claim that this study provides evidence that humans use a spatial / grid code for abstract knowledge like social knowledge.

This data does specifically not add anything new to this argument. As with almost all studies that test for a grid code in a similar "conceptual" space (not only the current study), the problem is that, when the space is not a uniform, square/circular space, and 2-dimensional then there is no reason the code will be perfectly grid like, i.e., show six-fold symmetry. In real world scenarios of social space (as well as navigation, semantic concepts), it must be higher dimensional - or at least more than two dimensional. It is unclear if this generalizes to larger spaces where not all part of the space is relevant. Modelling work from Tim Behrens' lab (e.g., Whittington et al., 2020) and Bradley Love's lab (e.g., Mok & Love, 2019) have shown/argued this to be the case. In experimental work, like in mazes from the Mosers' labs (e.g., Derdikman et al., 2009), or trapezoid environments from the O'Keefe lab (Krupic et al., 2015), there are distortions in mEC cells, and would not pass as grid cells in terms of the six-fold symmetry criterion.

The authors briefly discuss the limitations of this at the very end but do not really say how this speaks to the goal of their study and the claim that social space or knowledge is organized as a grid code and if it is in fact used in the brain in their study and beyond. This issue deserves to be discussed in more depth, possibly referring to prior work that addressed this, and raise the issue for future work to address the problem - or if the authors think it is a problem at all.

<https://doi.org/10.7554/eLife.89025.2.sa0>

Author Response

The following is the authors' response to the original reviews.

We would like to first thank the Editor as well as the two reviewers for their enthusiasm and careful evaluation of our manuscript. We also appreciate their thoughtful and constructive comments and suggestions. They did, however, have concerns regarding experimental design, data analysis, and over-interpretation of our findings. We endeavored to address these concerns through refinement of our framing, inclusion of additional new analyses, and rewriting some parts of our discussion section. We hope our response can better explain the rationale of our experimental design and data interpretation. In addition, we also acknowledge the limitations of our present study, so that it will benefit future investigations into this topic. Our detail responses are provided below.

Reviewer #1 (Public Review)

This study examines whether the human brain uses a hexagonal grid-like representation to navigate in a non-spatial space constructed by competence and trustworthiness. To test this, the authors asked human participants to learn the levels of competence and trustworthiness for six faces by associating them with specific lengths of bar graphs that

indicate their levels in each trait. After learning, participants were asked to extrapolate the location from the partially observed morphing bar graphs. Using fMRI, the authors identified brain areas where activity is modulated by the angles of morphing trajectories in six-fold symmetry. The strength of this paper lies in the question it attempts to address. Specifically, the question of whether and how the human brain uses grid-like representations not only for spatial navigation but also for navigating abstract concepts, such as social space, and guiding everyday decision-making. This question is of emerging importance.

Thanks very much again for the evaluation and comments. Please find our revision plans to each comment below.

The weak points of this paper are that its findings are not sufficiently supporting their arguments, and there are several reasons for this:

(1) Does the grid-like activity reflect 'navigation over the social space' or 'navigation in sensory feature space'? The grid-like representation in this study could simply reflect the transition between stimuli (the length of bar graphs). Participants in this study associated each face with a specific length of two bars, and the 'navigation' was only guided by the morphing of a bar graph image. Moreover, any social cognition was not required to perform the task where they estimate the gridlike activity. To make social decision-making that was conducted separately, we do not know if participants needed to navigate between faces in a social space. Instead, they can recall bar graphs associated with faces and compute the decision values by comparing the length of bars. Notably, in the trust game in this study, competence and trustworthiness are not equally important to make a decision (Equation 1). The expected value is more sensitive to one over the other. This also suggests that the space might not reflect social values but perceptual differences.

The Reviewer raises an interesting point. We apologize for not being clear enough to address this possibility in our original manuscript and we will improve the clarity in our revision. To address this issue, we would like to break it into two sub-questions and answer them separately: 1) Are participants merely memorizing the values associated with each avatar or do they place the avatars on a two-dimensional map in their internal representation. 2) If so, are the two dimensions of this internal representation social dimensions relating to competence and trust or sensory dimensions relating to bar height (i.e., social space or sensory space).

For the first question, we hope our analysis of the distance effect on the reaction time in the comparison task can address this issue. Specifically, it came from the idea that distance is a measure of similarity between two avatars in the 2D social space. The closer two avatars are, the more similar they are, hence distinguishing them will be harder and result in longer reaction time. If participants are merely memorizing the avatars as six isolated instances without integrating them into a low-dimensional map, then avatars should be equidistant (as if they were lying on the vertices of a 5-simplex), and would not show a distance effect. Therefore, we interpreted the stronger distance effect as a behavioural index of having a better internal map-like representation. This approach is adopted from the work by Park et al. (2020), where they used the distance effect to demonstrate human brains map abstract relationships among entities from piecemeal learning.

For the second question of 'social space' vs. 'sensory space', our study adopted the paradigm developed by, in which they used a similar way to construct a conceptual space and found that such space can be represented with grid-like code in the entorhinal and prefrontal cortex. We stayed close to the original design by Constantinescu et al. (2016) and hoped that our work could provide, to some extent, a close replication of their result but using non-

spatial social concepts instead. Indeed, this led to the limitation of our study that participants are passively traversing the artificial space rather than actively navigating in the space to make decisions/inferences. And we did not find sufficient evidence as reported in previous grid-like coding fMRI studies. This may have to do with low signal quality in the medial temporal region, we are not entirely sure. Nevertheless, we don't think our findings contradict or disprove previous findings in any way. Here we would also like to point to the work by Park et al. (2021). Their task involves making novel inferences in a 2D social hierarchy space and found that grid-like code in the entorhinal cortex and medial prefrontal cortex support such novel inferences. Hence, we argue that results from these studies and partial evidence from our study collectively support the idea that the entorhinal is important for representing abstract knowledge (spatial and non-spatial).

(2) Does the brain have a common representation of faces in a social space? In this study, participants don't need to have a map-like representation of six faces according to their levels of social traits. Instead, they can remember the values of each trait. The evidence of neural representations of the faces in a 2-dimensional social space is lacking. The authors argued that the relationship between the reaction times and the distances between faces provides evidence of the formation of internal representations. However, this can be found without the internal representation of the relationships between faces. If the authors seek internal representations of the faces in the brain, it would be important to show that this representation is not simply driven by perceptual differences between bar graphs that participants may recall in association with each face.

Considering these caveats, it is hard for me to agree if the authors provide evidence to support their claims.

With regard to the common representation of faces, this is a potential limitation of our paradigm because our current task design didn't include a stage of face presentation to properly test this question. With regard to the asymmetry between the two dimensions in determining expected value. We think that the prerequisite for identifying six-fold grid-like coding is to have an abstract space formed by orthogonal dimensions, i.e., competence and trustworthiness in our task are not correlated. In addition, the scanner task does not require computation of expected value. However, we do think that it is worth investigating whether the extent to which each dimension contributes to decision-making and inference will distort the grid-like representation of the map. Our prediction is that the entorhinal cortex will maintain a representation of the map invariant to this aspect so that it can support inferences in different contexts where different weights may be assigned to different dimensions. But this will be an interesting hypothesis for future studies to test. We hope that our revision plans with above considerations could address the Reviewer's comments.

Reviewer #2 (Public Review)

Summary:

In this work, Liang et al. investigate whether an abstract social space is neurally represented by a grid-like code. They trained participants to 'navigate' around a two-dimensional space of social agents characterized by the traits of warmth and competence, then measured neural activity as participants imagined navigating through this space. The primary neural analysis consisted of three procedures: 1) identifying brain regions exhibiting the hexagonal modulation characteristic of a grid-like code, 2) estimating the orientation of each region's grid, and 3) testing whether the strength of the univariate neural signal increases when a participant is navigating in a direction aligned with the grid, compared to a direction that is misaligned with the grid.

From these analyses, the authors find the clearest evidence of a grid-like code in the prefrontal cortex and weaker evidence in the entorhinal cortex.

Strengths:

The work demonstrates the existence of a grid-like neural code for a socially-relevant task, providing evidence that such coding schemes may be relevant for a variety of two-dimensional task spaces.

Thank you very much again for your careful evaluation and thoughtful comments. Please find our response to the comments below.

Weaknesses:

In various parts of this manuscript, the authors appear to use a variety of terms to refer to the (ostensibly) same neural regions: prefrontal cortex, frontal pole, ventromedial prefrontal cortex (vmPFC), and orbitofrontal cortex (OFC). It would be useful for the authors to use more consistent terminology to avoid confusing readers.

Thanks for pointing out the use of terms, we will try to improve that in the revision of our manuscript.

Claims about a grid code in the entorhinal cortex are not well-supported by the analyses presented. The whole-brain analysis does not suggest that the entorhinal cortex exhibits hexagonal modulation; the strength of the entorhinal BOLD signal does not track the putative alignment of the grid code there; multivariate analyses do not reveal any evidence of a grid-like representational geometry.

On a conceptual level, it is not entirely clear how this work advances our understanding of gridlike encoding of two-dimensional abstract spaces, or of social cognition. The study design borrows heavily from Constantinescu et al. 2016, which is itself not an inherent weakness, but the Constantinescu et al. study already suggests that grid codes are likely to underlie two-dimensional spaces, no matter how abstract or arbitrary. If there were a hypothesis that there is something unique about how grid codes operate in the social domain, that would help motivate the search for social grid codes specifically, but no such theory is provided. The authors do note that warmth and competence likely have ecological importance as social traits, but other past studies have used slightly different social dimensions without any apparent loss of generality (e.g., Park et al. 2021). There are some (seemingly) exploratory analyses examining how individual difference measures like social anxiety and avoidance might affect the brain and behavior in this study, but a strong theoretical basis for examining these particular measures is lacking.

We acknowledge that we used very similar dimensions to the work by Park et al. (2021). While Park and colleagues (2021) took a more innovative and rigorous approach, we tried to stay close to the original design by Constantinescu et al. (2016) with the hope that our work could provide, to some extent, a close replication of their result. Our data was collected before the 2021 paper came out and as the comment points out, we did not find as complete and convincing evidence as in these previous grid-like coding fMRI papers. This may be due to low signal quality in the medial temporal region, we are not entirely sure. But we don't think our current findings can contradict or disprove previous findings in any way.

I found it difficult to understand the analyses examining whether behavior (i.e., reaction times) and individual difference measures (i.e., social anxiety and avoidance) can be predicted by the hexagonal modulation strength in some region X, conditional on region X having a similar estimated grid alignment with some other region Y. It is possible that I

have misunderstood the authors' logic and/or methodology, but I do not feel comfortable commenting on the correctness or implications of this approach given the information provided in the current version of this manuscript.

We apologize for not being clear enough in the manuscript and we will improve the clarity in our revision. This exploratory analysis aims to examine if there is any correlation between the strength of grid-like representation of social value map and behavioral indicators of map-like representation; and test if there are any correlation between the strength of grid-like representation of this social value map and participants' social trait. For the behavioral indicator, we used the distance effect in the reaction time of the comparison task outside the scanner. The closer a pair of avatars are, the more similar they are, hence distinguishing them will be harder and results in longer reaction time when making comparison judgement. If participants are merely memorizing the avatars as six isolated instances without integrating them into a map, all avatars should be equidistant and there wouldn't be a distance effect. We interpreted stronger grid-like activity as a neural index of better representation of the 2D social space, and we interpreted stronger distance effect as a behavioral index of having better internal map-like representation.

It was puzzling to see passing references to multivariate analyses using representational similarity analysis (RSA) in the main text, given that RSA is only used in analyses presented in the supplementary material.

We speculate if RSA in entorhinal ROI would be more sensitive than the wholebrain univariate analysis to identify grid-like code because a previous paper on grid-like code in olfactory space (Bao et al., 2019) didn't identify grid-like representation with univariate analysis but identified it with RSA analysis. However, we failed to find evidence of grid-like code in the entorhinal ROI aligned to its own putative grid orientation with the RSA approach. We reported this result in the main text to show that we carried out a relatively thorough investigation to test the hypothesis using various approaches and decided to add references to the RSA approach in the main text as well.

Reviewer #3 (Public Review)

Liang and colleagues set out to test whether the human brain uses distance and grid-like codes in social knowledge using a design where participants had to navigate in a two-dimensional social space based on competence and warmth during an fMRI scan. They showed that participants were able to navigate the social space and found distance-based codes as well as grid-like codes in various brain regions, and the grid-like code correlated with behavior (reaction times).

On the whole, the experiment is designed appropriately for testing for distant-based and grid-like codes and is relatively well-powered for this type of study, with a large amount of behavioral training per participant. They revealed that a number of brain regions correlated positively or negatively with distance in the social space, and found grid-like codes in the frontal polar cortex and posterior medial entorhinal cortex, the latter in line with prior findings on grid-like activity in the entorhinal cortex. The current paper seems quite similar conceptually and in design to previous work, most notably by Park et al., 2021, Nature Neuroscience.

Thanks very much again for your careful evaluation and comments. Please find our response to the comments below.

Below, I raise a few issues and questions on the evidence presented here for a grid-like code as the basis of navigating abstract social space or social knowledge.

(1) The authors claim that this study provides evidence that humans use a spatial / grid code for abstract knowledge like social knowledge.

This data does specifically not add anything new to this argument. As with almost all studies that test for a grid code in a similar "conceptual" space (not only the current study), the problem is that when the space is not a uniform, square/circular space, and 2-dimensional then there is no reason the code will be perfectly grid-like, i.e., show six-fold symmetry. In real-world scenarios of social space (as well as navigation, semantic concepts), it must be higher dimensional - or at least more than two-dimensional. It is unclear if this generalizes to larger spaces where not all part of the space is relevant. Modelling work from Tim Behrens' lab (e.g., Whittington et al., 2020) and Bradley Love's lab (e.g., Mok & Love, 2019) have shown/argued this to be the case. In experimental work, like in mazes from the Mosers' labs (e.g., Derdikman et al., 2009), or trapezoid environments from the O'Keefe lab (Krupic et al., 2015), there are distortions in mEC cells, and would not pass as grid cells in terms of the six-fold symmetry criterion.

The authors briefly discuss the limitations of this at the very end but do not really say how this speaks to the goal of their study and the claim that social space or knowledge is organized as a grid code and if it is in fact used in the brain in their study and beyond. This issue deserves to be discussed in more depth, possibly referring to prior work that addressed this, and raising the issue for future work to address the problem - or if the authors think it is a problem at all.


Thanks very much for the references to the papers that we haven't considered enough in our discussion. We will endeavour to discuss the topic in more depth in our revision. In summary, we raise this discussion point because various research groups have found gridlike representations in 2D artificial conceptual space. We think that the next step for a stronger claim would be to find the representation of more spontaneous non-spatial maps.

Data and analysis

(2) Concerning the negative correlation of distance with activation in the fusiform gyrus and visual cortex: this is a slightly puzzling but potentially interesting finding. However, could this be related to reaction times? The larger the distance, the longer the reaction times, so the original finding might reflect larger activations with smaller distances.

Thanks very much for the suggestion. However, we didn't find a correlation between response time in the choice stage in the scanner task and the negative distance activation in the fusiform gyrus (Figures below). Meanwhile, the morph period in each trial remains the same, the negative correlation of distance with activation in the fusiform gyrus could also be interpreted as a positive correlation of morphing speed with activation in the fusiform gyrus. Indeed, stronger negative activation indicates larger activation for smaller distances, but we are uncertain what it indicates concerning the functional role of Fusiform in our current task.

Author response image 1.



(3) Concerning the correlation of grid-like activity with behavior: is the correlation with reaction time just about how long people took (rather than a task-related neural signal)? The authors have only reported correlations with reaction time. The issue here is that the duration of reaction times also relates to the starting positions of each trial and where participants will navigate to. Considering the speed-accuracy tradeoff, could performance accuracy be negatively correlated with these grid consistency metrics? Or it could be positively correlated, which would suggest the grid signal reflects a good representation of the task.

We apologize for not being clear enough in the manuscript and we will improve the clarity in our revision. The reaction time used to calculate the distance effect is from a task outside the scanner. The closer a pair of avatars are, the more similar they are, hence distinguishing them will be harder and results in longer reaction time when making comparison judgement. If participants are merely memorizing the avatars as six isolated instances without integrating them into a map, all avatars should be equidistant and there wouldn't be a distance effect. We interpreted stronger grid-like activity as a neural index of better representation of the 2D social space, and we interpreted stronger distance effect as a behavioural index of having better internal map-like representation. This was the motivation behind this analysis.

References

- Bao, X., Gjorgieva, E., Shanahan, L. K., Howard, J. D., Kahnt, T., & Gottfried, J. A. (2019). Grid-like Neural Representations Support Olfactory Navigation of a Two-Dimensional Odor Space. *Neuron*, 102(5), 1066-1075 e1065. <https://doi.org/10.1016/j.neuron.2019.03.034>
- Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing conceptual knowledge in humans with a gridlike code. *Science*, 352(6292), 1464-1468. <https://doi.org/10.1126/science.aaf0941>

Park, S. A., Miller, D. S., & Boorman, E. D. (2021). Inferences on a multidimensional social hierarchy use a grid-like code. *Nat Neurosci*, 24(9), 1292-1301. <https://doi.org/10.1038/s41593-02100916-3>

Park, S. A., Miller, D. S., Nili, H., Ranganath, C., & Boorman, E. D. (2020). Map Making: Constructing, Combining, and Inferring on Abstract Cognitive Maps. *Neuron*, 107(6), 1226-1238 e1228. <https://doi.org/10.1016/j.neuron.2020.06.030>